

Lab-Tips[®] ESD Swab-LTP1465ESD ESD Knitted Polyester Swab with Long Handle

Cleanroom laundered double layer 100% polyester knit swab

The LTP1465ESD swab features an ESD long handle, engineered

with static dissipative polymer. It is a general purpose swab

specially suited for cleaning hard to reach areas. Its flexible

paddle tip and durable cleanroom laundered knit head are excel-

lent for rigorous cleaning applications.

Key Attributes

- Cleanroom laundered 100% continuous filament polyester knit head
- Long polypropylene handle with a flexible paddle head
- Laundered and packaged in ISO Class 4 {Class 10} cleanroom
- Static dissipative polypropylene handle with thermally bonded head

Benefits

- Critically low particles, fibers, ions and extractables
- High abrasion resistance for rigorous cleaning applications
- Excellent chemical resistance
- No contaminating adhesives
- Good sorbency
- Free from Silicone, amides and DOP
- Packaged in an anti-static bag

Environmental

Complies with RoHS and REACH requirements

Applications

- Designed for the highest level of contamination control in critical processing applications
- Cleaning of sensitive equipment
- Applying lubricants and other liquids
- Surface sampling
- Cleaning validation
- Static sensitive applications
- Cleaning with solvents

Physical Characteristics

Head Material	Knitted P	olyester	Handle Thickness	3.1mm	{0.122"}	
Head Width	7mm	{0.275"}	Handle Length	145mm	{5.71"}	
Head Thickness	4mm	{0.157"}	Total Swab Length	162mm	{6.38"}	
Head Length	16.8mm	{0.661"}	Head Bond	Thermal		
Handle Material	Polypropylene		Handle Text	Berkshire		
Handle Width	3.1mm	{0.122"}				

Other ESD Swabs

- LT070PESD Pointed Swab
- LT070RESD Short handle rigid head

rkshire.eu.com				
l 44 (0) 870 757 2877 perkshire.uk.com	Americas	Tel 1 413 528 2602	Fax 1 413 528 2614	info@berkshire.com
	Europe	Tel 44 (0) 870 757 2877	Fax 44 (0) 870 757 2878	enquiries@berkshire.uk.com
	SE Asia	Tel 65 6252 4313	Fax 65 6252 4312	enquiries@berkshire.com.sg
	lanan	Tel 81 3 5827 2380	Fax 81 3 5827 2382	master@herkshire.co.in

www.be Contact: Tel



Technical Data:

ATTRIBUTE		LTP1465ESD	TEST METHOD
Surface Resistivity of Handle	ohms	1.0 x 10 ⁹	ANSI/ESD STM 11.13
Volume Resistance of Handle	ohms	1.0 x 10 ⁸	ANSI/ESD STM 11.13
Non-Volatile Residue	IPA mg/swab	0.045	IEST-RP.CC004.3, Sec 7.1.2
lons (µg/swab)	Chloride	0.035	IEST-RP.CC004.3, Sec 7.2.2
	Sulfate	0.023	
	Nitrate	ND*	
	Phosphate	ND*	
	Fluoride	ND*	
	Potassium	0.044	
	Calcium	0.036	
	Sodium	0.015	
	Magnesium	0.0052	

Notes:

- Data shown are typical values
- Due to differences in test methods applied and equipment utilized by different swab manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- * ND* = below the detection limit of the equipment.

Order Information:

Product	Part Number	Size	Swabs/pk	Pks/cs	Case size
Long Handle ESD Polyester Swab	LTP1465ESD10	162mm	100	10	180 x 150 x 170mm



www.berkshire.eu.com

Contact: Tel 44 (0) 870 757 2877 / enquiries@berkshire.uk.com BC_5100_03-2015