

## Gamma Wipe® 300

Sterile Sealed Edge Cleanroom Laundered 100% Polyester

Gamma Wipe® 300 is a high sorbency, tubular, sealed edge cleanroom laundered two-ply wiper recommended for ISO Class 3 and above environments composed of 100% continuous filament polyester knit fabric.

Each package is gamma irradiated sterile to a 10<sup>-6</sup> Sterility Assurance Level. This combination of properties provides Gamma Wipe® 300 with the highest level of cleanliness, abrasion resistance and

chemical compatibility required for cleaning critical sterile processing environments.



### Key Attributes

- 100% continuous filament polyester knit
- Two-ply pinsonic tubular construction
- Patented sealed edge process for reduced fiber contamination; Patent #5,229,181
- Laundered and packaged in Berkshire's ISO Class 4 cleanroom with Lot Number on each pack
- Gamma irradiated and sterile validated to a 10<sup>-6</sup> Sterility Assurance Level per AAMI guidelines
- Header style packaging with Package Integrity testing
- Certificate of Sterility available to be down loaded on the web by lot number **24/7**. Details: Expiration Date, Radiation Dosage, Lot Information, Meets cGMP requirements for traceability

### Benefits

- Critically low particles, fibers, ions and extractables
- High absorbency
- Pinsonic design adds surface texture that aids in stubborn residue removal
- Patented sealed edge process combined with tubular design offers excellent abrasion resistance for the toughest cleaning applications
- Chemically compatible with common cleaning and disinfecting solutions including isopropyl alcohol, phenols, bleaches and quarternary ammonium compounds

### Other Sterile wipers

- Gamma Wipe SuperSorb®
- Gamma Wipe® 120
- Gamma Wipe® 67

### Environmental

- Complies with RoHS

### Applications

- Designed for use in ISO Class 3 and higher sterile environments where microbial exclusion is demanded
- Designed for cleaning sterile surfaces and equipment during aseptic processing

### Pre-Wetted Option

The same wiper material can be provided in pre-wetted formats for reduced VOC emissions, increased convenience, increased productivity, improved solvent control and cleaning protocol repeatability and reduced costs. Pre-wetted options include WFI.

### Validated Sterile

ANSI/AAMI/ISO procedures have been followed for verification of irradiation dose with audits being performed to monitor bioburden levels and dose. The Sterility Assurance Level (SAL) or the probability of a viable organism being present on a product unit after sterilization is a SAL of 10<sup>-6</sup> (which is the chance of 1 non-sterile unit in 1,000,000).

[www.berkshire.eu.com](http://www.berkshire.eu.com)

Contact: Tel 44 (0) 870 757 2877  
enquiries@berkshire.uk.com

America	Tel 1 413 528 2602	Fax 1 413 528 2614	info@berkshire.com
Europe	Tel 44 (0) 870 757 2877	Fax 44 (0) 870 757 2878	enquiries@berkshire.uk.com
SE Asia	Tel 65 6252 4313	Fax 65 6252 4312	enquiries@berkshire.com.sg
Japan	Tel 81 3 5827 2380	Fax 81 3 5827 2382	master@berkshire.co.jp

## Technical Data:

Attribute		Units	Value	Test Method
Basis Weight		g/m <sup>2</sup>	189	TAPPI T-410
Caliper		µm	552	TAPPI T-411
Fibers	≥100µm	fibers/cm <sup>2</sup>	0.0075	IEST-RP-CC004.3, Sec 6.1.3 / Sec 6.2.2
Particles	≥0.5µm	x10 <sup>3</sup> /cm <sup>2</sup>	0.55	IEST-RP-CC004.3, Sec 6.1.3 / Sec 6.2.1
Sorbency	Capacity	mL/m	522	IEST-RP-CC004.3, Sec 8.1 modified / Sec 8.2 modified
	Efficiency	mL/g	2.8	
	Rate	seconds	1	
Non-Volatile Residue	DI Water	g/m <sup>2</sup>	0.0047	IEST-RP-CC004.3, Sec 7.1.2
	IPA	g/m <sup>2</sup>	0.025	
Ions	Na <sup>+</sup>	ppm	0.0049	IEST-RP-CC004.3, Sec 7.2.2
	K <sup>+</sup>	ppm	0.041	
	Ca <sup>++</sup>	ppm	0.0086	
	Mg <sup>++</sup>	ppm	0.0025	
	Cl <sup>-</sup>	ppm	0.023	

### Notes:

- Technical data represented in this table are typical values at the time of publication. These should not be used as product specifications.
- Due to differences in test methods applied and equipment utilized by different wiper manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions
- Third party testing can be performed upon request

## Order Information:

Product	Number	Size	Shts/pk	Pks/Inner bag	Inner bags/cs	Pks/cs	Style
Gamma Wipe® 300	GW300.ST.25	12x12"(30x30cm)	10	5	5	25	Header Bag

## Other Berkshire Products



Wipers




Mop Systems



Face Masks



Glove Liners



Documentation Systems



Swabs